

WHAT IS CLAIMED IS:

1 1. A method of facilitating interoperability between two networks, the
2 method comprising:
3 providing a VHN network having a VHN element;
4 providing a HAVi network having a HAVi element; and
5 translating messages via a protocol translator coupled with the VHN network
6 and the HAVi network;
7 wherein the interoperability is facilitated between the HAVi element and the
8 VHN element.

1 2. The method of claim 1, wherein the protocol translator comprises:
2 a HAVi bridge control manager;
3 a VHN bridge control manager coupled with the HAVi bridge control
4 manager; and
5 a HAVi-VHN DCM coupled with the VHN bridge control manager.

1 3. A method of facilitating interoperability between two networks, the
2 method comprising:
3 providing a VHN network having a VHN element;
4 providing a HAVi network having a HAVi element;
5 providing a protocol translator coupled with the VHN network and the HAVi
6 network; and
7 controlling the HAVi element with the VHN element.

1 4. The method of claim 3, wherein the protocol translator comprises:
2 a HAVi bridge control manager;
3 a VHN bridge control manager coupled with the HAVi bridge control
4 manager; and
5 a HAVi-VHN DCM coupled with the VHN bridge control manager.

1 5. A method of facilitating interoperability between two networks, the
2 method comprising:
3 providing a VHN network having a VHN element;
4 providing a HAVi network having a HAVi element;

providing a protocol translator coupled with the VHN network and the HAVi network; and

controlling the VHN element with the HAVi element.

6. The method of claim 5, wherein the protocol translator comprises:

- a HAVi bridge control manager;
- a VHN bridge control manager coupled with the HAVi bridge control manager; and
- a HAVi-VHN DCM coupled with the VHN bridge control manager.

7. The method of claim 5, wherein controlling comprises controlling a HAVi device with a VHN device.

8. The method of claim 5, wherein controlling comprises controlling a HAVi device with a VHN application.

9. The method of claim 5, wherein controlling comprises controlling a HAVi application with a VHN device.

10. The method of claim 5, wherein controlling comprises controlling a HAVi application with a VHN application.

11. A computer-readable media for facilitating interoperability between a VHN network having a VHN element and a HAVi network having a HAVi element, the computer-readable media comprising:

- providing instructions for coupling the VHN network with the HAVi network;
- and
- providing instructions for facilitating interoperability between the HAVi element and the VHN element.

12. The computer-readable media of claim 11, wherein providing instructions for facilitating interoperability comprises:

- providing instructions for a HAVi bridge control manager;
- providing instructions for a VHN bridge control manager coupled with the HAVi bridge control manager; and

09790289-020303
T08020-68208260

6 providing instructions for a HAVi-VHN DCM coupled with the VHN bridge
7 control manager.

1 13. A system for facilitating interoperability between two networks, the
2 system comprising:

3 a VHN network having a VHN element;
4 a HAVi network having a HAVi element; and
5 a protocol translator coupled with the VHN network and the HAVi network;
6 wherein the protocol translator facilitates interoperability between the HAVi
7 element and the VHN element.

1 14. The system of claim 13, wherein the protocol translator comprises:
2 a HAVi bridge control manager;
3 a VHN bridge control manager coupled with the HAVi bridge control
4 manager; and
5 a HAVi-VHN DCM coupled with the VHN bridge control manager.